

52-WHT/BSE/CLR

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET
00

removed by abrasive blasting, sanding, or grinding.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Primary irritant.

SKIN: N/A

INHALATION: With poor ventilation, vapor or spray mist may irritate
respiratory mucous membranes, causing headache & nausea.

INGESTION: N/A

CHRONIC HEALTH HAZARDS

Long term overexposure to crystalline silica causes silicosis, a form
of pulmonary fibrosis. Continued overexposure to silica can lead to
cardiopulmonary impairment.

ROUTE(S) OF EXPOSURE

Exposure may be inhalation and/or skin or eye contact, depending on
conditions of use.

CARCINOGENICITY

IARC and NTP have reviewed crystalline silica. Crystalline silica
is listed with IARC as Group 1 (carcinogenic to humans). IARC found
sufficient evidence in humans for the carcinogenicity of inhaled
crystalline silica in the form of quartz or cristobalite from
occupational sources.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at
least 15 minutes and get medical attention.

SKIN CONTACT: Remove from skin with soap and water. Remove drenched
clothing. If irritation persists, consult a physician.

INHALATION: If affected by inhalation of vapor or spray mist, remove to
fresh air. If necessary, restore breathing; in this case
contact physician at once.

INGESTION: If victim is conscious, give 2 glasses of water to dilute.
Do not induce vomiting. Consult physician or poison control
center at once.

NOTE TO PHYSICIAN:

Not Applicable.

52-WHT/BSE/CLR

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET
00

HAZARDOUS PRODUCTS OF DECOMPOSITION

Heating to decomposition, as in a fire or welding, may produce hazardous fumes. Fumes may contain carbon monoxide, carbon dioxide and oxides of nitrogen.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : N/A
DOT PACKAGING GROUP : N/A
DOT LABEL : NONE
DOT SHIPPING NAME : PAINT
DOT PLACARD : NONE
UN/NA NUMBER : NONE

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

2-BUTOXYETHANOL
CAS# 111-76-2 PCT BY WT: 4.7320

52-WHT/BSE/CLR

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET
00

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 09/12/2005
Last Revision Date : 04/16/2003

MSDS Prepared for :

MSDS Last Prepared : NONE
HMIS Rating: Health- 1 Flammability- 0
Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g)(4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.