

55-145

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET
1

CA PROPOSITION 65: No

5 LT AROMATIC SOLVENT, NAPHTHA

CAS# 64742-95-6

AROMATIC PETROLEUM DISTILLATES

PCT BY WT: .5 - 5 VAPOR PRESSURE: 3.000 MMHG @ 68F

EXPOSURE LIMIT:

ACGIH TLV/TWA: NE

OSHA PEL/TWA: NE

CA PROPOSITION 65: Yes

6

CAS# 64742-88-7

MINERAL SPIRITS

PCT BY WT: 5 - 10 VAPOR PRESSURE: 2.000 MMHG @ 68F

EXPOSURE LIMIT:

ACGIH TLV/TWA: TWA 100 ppm

OSHA PEL/TWA: TWA 100 ppm

This product contains one or more reported carcinogens or suspected carcinogens which are noted in Section 3, Hazards Identification, CARCINOGENICITY.

This product contains one or more Hazardous Air Pollutants.

This product contains pigments, which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: May cause eye damage and pain.

SKIN: May irritate skin.

INHALATION: Anesthetic. Nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May irritate nose, throat and respiratory tissue.

INGESTION: Swallowing small amounts of this product during normal handling is not likely to cause harmful effects, but swallowing large amounts may be harmful.

CHRONIC EFFECTS

NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause respiratory and/or skin sensitization.

55-145

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET
1

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Any pre-existing respiratory or eye/skin conditions.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

IARC lists cobalt and cobalt compounds as possible human carcinogens (Group 2B). However, there is inadequate evidence of the carcinogenicity of cobalt and cobalt compounds in humans.

ACGIH has given cobalt a rating of A3, animal carcinogen. They state that available epidemiological studies do not confirm an increased risk of cancer in exposed humans.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

SKIN CONTACT: Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air. If necessary, restore breathing; in this case contact physician at once.

INGESTION: If victim is conscious, give 2 glasses of water to dilute. Do not induce vomiting. Consult physician or poison control center at once.

NOTE TO PHYSICIAN:

Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification : Class 1B
Flashpoint : 50.0 °F
Explosion Level : Low - .9
High - 7.0

EXTINGUISHING MEDIA

Use National Fire Protection Association (NFPA) Class B extinguisher (carbon dioxide, dry chemical or foam) designed to extinguish NFPA Class 1B flammable liquid fires.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT

Clear fire area of unprotected personnel. Do not enter confined space

without helmet, face shield, bunker coat, gloves, rubber boots, and a positive pressure NIOSH-approved self-contained breathing apparatus. Water spray may be used to cool closed containers to prevent pressure build-up and possible explosion when exposed to extreme heat. Water may be ineffective in extinguishing a paint fire. Therefore, use caution not to spread flames with stream of water. If water is used, fog nozzles are preferable.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Vapors may be heavier than air and may travel along the ground to distant ignition sources, then flash back to the vapor source. Keep welding or cutting equipment away from product. Containers may explode when exposed to extreme heat.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition (flame, hot surfaces and sources of electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. For large spills in a confined area, use self-contained non-sparking tools. Keep out of drains, sewers and waterways.

CLEAN-UP

Contain and remove with inert absorbent and non-sparking tools.

SECTION 7 - HANDLING AND STORAGE

HANDLING

Keep away from heat, sparks and open flame. Use only with adequate ventilation. Keep from contact with oxidizing materials. Comply with all national, state, and local codes pertaining to the storage, handling dispensing and disposal of flammable liquids.

STORAGE

Do not store above 120 Degrees F. Close container after each use.

SPECIAL COMMENTS

Do not take internally. Wash with soap and water before eating, drinking, smoking or using toilet.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV of the most hazardous ingredient in Section 2, below acceptable limit, and LEL in Section 5 below stated limit, during application of this product, and to remove decomposition products

55-145

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET
1

hazardous fumes. Fumes may contain carbon monoxide, carbon dioxide and oxides of nitrogen.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : 3
DOT PACKAGING GROUP : PG II
DOT LABEL : FLAMMABLE LIQUID
DOT SHIPPING NAME : PAINT
DOT PLACARD : FLAMMABLE LIQUID
UN/NA NUMBER : UN1263

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

COBALT 2-ETHYLHEXANOATE

CAS# 136-52-7 PCT BY WT: .1720

1,2,4-TRIMETHYLBENZENE

CAS# 95-63-6 PCT BY WT: 2.3680

55-145

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET
1

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 09/12/2005
Last Revision Date : 02/06/2003

MSDS Prepared for :

MSDS Last Prepared : NONE
HMIS Rating: Health- 2* Flammability- 2
Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g)(4).
The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m3 or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.