



**CORONADO**  
P A I N T

**SECTION NO. 1**  
**ADS -212**  
**1226 LINE**  
Rev. 02/11



**Air Care™**  
**Zero VOC\* Interior Acrylic Flat**  
**1226 Line**

<b>Type</b> Vinyl Acrylic	<b>Sheen</b> Flat	<b>Theoretical Spread Rate</b> 350 to 450 Sq. Ft. Per Gallon**	<b>Recommended Application</b> Brush, Roller or Airless Spray	<b>Thinner</b> Clean Water	<b>Clean Up</b> Warm Soapy Water
<b>Dry Time:</b>		<b>Tack Free:</b> 30 Minutes	<b>Recoat:</b> 4 Hours	<b>Full Cure:</b> 10 Days	

<b>PRODUCT NAME:</b> 1226 Line Air Care™ Zero VOC* Interior Acrylic Flat	CORONADO® Air Care™ Acrylic Flat incorporates the latest raw materials and coatings technology into a completely odorless and VOC free* product. It is absolutely free of solvents* and thus conforms to all national, state and local VOC and air quality regulations. Air Care™ can be used for interior painting in occupied areas without disrupting the normal course of business or recreation. It is spatterless during application, flows easily, has excellent hiding power, dries quickly and cleans up readily with soap and water. The cured film will withstand repeated washing.	
<b>WHERE TO USE:</b>	<b>Drywall</b> <b>Plaster</b> <b>Wood</b> <b>Metal</b> <b>Masonry</b>	This product is ideally suited for painting walls and ceilings where an eye appealing flat finish is desired. It can be applied to existing finishes as well as to properly prepared and primed wood, metal and masonry surfaces. Air Care™ Acrylic Flat can be used for residential or commercial applications.
<b>* VOC STATEMENT:</b>	Solvent Free Before Tinting: When Air Care is tinted using standard universal colorants, the addition of colorant will add VOC's to the final product and color.	

<b>REGULATORY INFORMATION:</b>	<b>VOC/VOS STATEMENT:</b>	<b>OTC CATEGORY:</b>	<b>MPI / LEED:</b>
	The products supported by this data sheet contain a maximum of 2 grams per liter VOC / VOS (0.02 lbs/gal.) excluding water & exempt solvents, before tinting.	This product is compliant under the Ozone Transport Commission regulations as a Flat Coating.	This product is certified under MPI #143. This product does meet qualifications for LEED (Leadership in Energy and Environmental Design) projects.

<b>SURFACE PREPARATION:</b>	<p>The surface to be painted must be clean, dry and free of dirt, chalk, wax, grease, rust, mildew, flaking paint or any other surface contamination that could affect product performance. Dirt and chalk should be removed by cleaning thoroughly with warm, soapy water followed by a clean water rinse. Mildew must be removed by washing with a solution of one part household bleach and three parts water. Rinse well and allow to dry. Grease and oils should be removed by cleaning with Sur-Prep™ I Emulsifier. Remove loose paint by scraping. Feather sand rough edges to ensure a smooth finish coat. Sanding should dull glossy surfaces. Any exposed substrate should be spot primed using the appropriate primer. Water stains should be sealed using 119-11 Cover – It™.</p> <p><b>Priming (New or Bare Surfaces):</b>  <b>Plaster/Drywall</b> – Use 1240-11 Odorless Primer Sealer  <b>Wood</b> – Use 78-11 Latex Undercoater  <b>Smooth Masonry</b> – Use 1240-11 Odorless Primer Sealer  <b>Masonry Block</b> – Use 958-11 Acrylic Block Filler  <b>Metal</b> – Use 36-11 Metal Primer or 180-11 DTM Primer</p>
-----------------------------	---

<b>APPLICATION:</b>	Stir product thoroughly with a circular, lifting motion. Air-Care™ Acrylic Flat may be applied by brush, roller or spray at a rate of up to 450 square feet per gallon. For brush application, use a quality brush with a synthetic filament. When rolling, use a roller cover with a depth of pile matched to the texture of the surface being painted. If applying by airless spray, a tip size of .017 to .019 will generally provide the most satisfactory results. For spraying, Air Care™ can be thinned up to 15% with clean water. Apply only when surface, ambient and material temperatures are above 50° F. Clean tools and equipment thoroughly with warm, soapy water followed by a clean water rinse.
<b>** NOTE ON SPREAD RATE:</b>	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
<b>IMPORTANT NOTE:</b>	Air Care™ Acrylic Flat can be tinted with up to 2 ounces of Universal Tinting Color per gallon BUT tinting will add small amounts of volatile organic compounds (VOC's). Tinting will not affect the odorless properties of this material.
<b>RESIN TYPE:</b>	Ethylene Vinyl Acetate Emulsion Polymer
<b>SOLIDS:</b>	Weight: 54.9 ± 1.0% Volume: 36.5 ± 1.0%
<b>WEIGHT PER GALLON:</b>	11.7 lbs.
<b>VISCOSITY:</b>	100 - 107 KU (Krebs Units)
<b>FLASH POINT:</b>	200° F. or greater (TT-P-141, Method 4293)
<b>SPECULAR GLOSS:</b>	0 – 3 units @ 85 degrees
<b>SAG RATING:</b>	13+ mils (Leneta)
<b>REC. FILM THICKNESS:</b>	Wet: 3.6 to 4.6 mils Dry: 1.3 to 1.7 mils
<b>LIGHT REFLECTANCE:</b>	89% (White and light colors)
<b>CAUTIONS:</b>	<p style="text-align: center;"><b>WARNING!</b> HARMFUL IF INHALED.</p> <p><b>Use only with adequate ventilation.</b> Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Wash thoroughly after handling. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.</p> <p style="text-align: center;">Keep away from heat and flame.</p> <p style="text-align: center;"><b>Obtain and read the MSDS prior to using this product.</b> <b>KEEP OUT OF REACH OF CHILDREN</b></p>