



CORONADO
P A I N T

SECTION NO. 1
ADS -212
1226 LINE



Air Care™
Zero VOC Interior Acrylic Flat
1226 Line

Type	Sheen	Theoretical Spread Rate	Recommended Application	Thinner	Clean Up
Vinyl Acrylic	Flat	350 to 450 Sq. Ft. Per Gallon*	Brush, Roller or Airless Spray	Clean Water	Warm Soapy Water
Dry Time:		Tack Free: 30 Minutes	Recoat: 4 Hours	Full Cure: 10 Days	

PRODUCT NAME: 1226 Line Air Care™ Zero VOC Interior Acrylic Flat	CORONADO® Air Care™ Acrylic Flat incorporates the latest raw materials and coatings technology into a completely odorless and VOC free product. It is absolutely free of solvents and thus conforms to all national, state and local VOC and air quality regulations. Air Care™ can be used for interior painting in occupied areas without disrupting the normal course of business or recreation. It is spatterless during application, flows easily, has excellent hiding power, dries quickly and cleans up readily with soap and water. The cured film will withstand repeated washing.	
WHERE TO USE:	Drywall Plaster Wood Metal Masonry	This product is ideally suited for painting walls and ceilings where an eye appealing flat finish is desired. It can be applied to existing finishes as well as to properly prepared and primed wood, metal and masonry surfaces. Air Care™ Acrylic Flat can be used for residential or commercial applications.
SURFACE PREPARATION:	<p>The surface to be painted must be clean, dry and free of dirt, chalk, wax, grease, rust, mildew, flaking paint or any other surface contamination that could affect product performance. Dirt and chalk should be removed by cleaning thoroughly with warm, soapy water followed by a clean water rinse. Mildew must be removed by washing with a solution of one part household bleach and three parts water. Rinse well and allow to dry. Grease and oils should be removed by cleaning with Sur-Prep™ I Emulsifier. Remove loose paint by scraping. Feather sand rough edges to ensure a smooth finish coat. Sanding should dull glossy surfaces. Any exposed substrate should be spot primed using the appropriate primer. Water stains should be sealed using 119-11 Cover – It™.</p> <p>Priming (New or Bare Surfaces): Plaster/Drywall – Use 1240-11 Odorless Primer Sealer Wood – Use 78-11 Latex Undercoater Smooth Masonry – Use 1240-11 Odorless Primer Sealer Masonry Block – Use 958-11 Acrylic Block Filler Metal – Use 36-11 Metal Primer or 180-11 DTM Primer</p>	
APPLICATION:	Stir product thoroughly with a circular, lifting motion. Air-Care™ Acrylic Flat may be applied by brush, roller or spray at a rate of up to 450 square feet per gallon. For brush application, use a quality brush with a synthetic filament. When rolling, use a roller cover with a depth of pile matched to the texture of the surface being painted. If applying by airless spray, a tip size of .017 to .019 will generally provide the most satisfactory results. For spraying, Air Care™ can be thinned up to 15% with clean water. Apply only when surface, ambient and material temperatures are above 50° F. Clean tools and equipment thoroughly with warm, soapy water followed by a clean water rinse.	

* NOTE ON SPREAD RATE:	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.
IMPORTANT NOTE:	Air Care™ Acrylic Flat can be tinted with up to 2 ounces of Universal Tinting Color per gallon BUT tinting will add small amounts of volatile organic compounds (VOC's). Tinting will not affect the odorless properties of this material.
RESIN TYPE:	Ethylene Vinyl Acetate Emulsion Polymer
SOLIDS:	Weight: 54.9 ± 1.0% Volume: 36.5 ± 1.0%
WEIGHT PER GALLON:	11.7 lbs.
VISCOSITY:	100 - 107 KU (Krebs Units)
FLASH POINT:	200° F. or greater (TT-P-141, Method 4293)
SPECULAR GLOSS:	0 – 3 units @ 85 degrees
SAG RATING:	13+ mils (Leneta)
REC. FILM THICKNESS:	Wet: 3.6 to 4.6 mils Dry: 1.3 to 1.7 mils
LIGHT REFLECTANCE:	89% (White and light colors)
CAUTIONS:	<p style="text-align: center;">WARNING! HARMFUL IF INHALED.</p> <p style="text-align: center;">Use only with adequate ventilation. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Wash thoroughly after handling. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.</p> <p style="text-align: center;">Keep away from heat and flame.</p> <p style="text-align: center;">Obtain and read the MSDS prior to using this product. KEEP OUT OF REACH OF CHILDREN</p>
VOC/VOS STATEMENT:	This product contains a maximum of 1 gram VOC/VOS per liter of coating. (0.01 pounds per gallon).
OTC CATEGORY:	This product is compliant under the Ozone Transport Commission regulations as a Flat Coating in all container sizes.

05/09