



101 Paragon Drive · Montvale, New Jersey 07645 · PHONE 800-883-4193 · FAX 800-394-9022

MAXUM-PREP™ SPRAY FORMULA DECK & WOOD STRIPPER

Type	Dilution Ratio:	Theoretical Spread Rate	Recommended Application	Thinner	Clean Up
Spray Formula Stripper	None	Up to 150 Sq. Ft. per Gallon*	MAXUM® Pump Style Sprayer, Low Pressure Airless	Water	Water

PRODUCT NAME: M95-2000 MAXUM PREP™ Spray Formula Deck & Wood Stripper	MAXUM-PREP™ Spray Formula Deck & Wood Stripper- is a ready to use, biodegradable stripper developed to remove acrylic and solvent based stains and transparent wood finishes from pine, cedar, redwood, and pressure treated lumber decks, fencing, and siding. After using MAXUM-PREP™ Spray Formula Deck & Wood Stripper on cedar, redwood, and other tannin bleeding woods, we recommend neutralizing the surface with MAXUM-PREP™ Wood Brightener.	
WHERE TO USE:	Decks Fences Railings Shingles Vertical Siding	MAXUM-PREP™ can be used on all types of acrylic and solvent based stains that have been applied to pressure treated wood, cedar, pine, redwood, and T-111 siding on both vertical and horizontal surfaces.
SURFACE PREPARATION:	Before applying Spray Formula Deck & Wood Stripper, remove all furniture, metal fixtures and children's toys from the area. DO NOT apply to painted aluminum, vinyl, or other painted surfaces. If stripper comes into contact with these surfaces, rinse immediately to avoid damage and/or discoloration. To avoid damage to vegetation, thoroughly wet down with water prior to application and rinse thoroughly after application.	
APPLICATION:	<p>Prior to application test product in an inconspicuous area and allow to dry thoroughly before use. Surface must be dry and above 50°F.</p> <p>Surfaces will be extremely slippery during the application and rinsing process.</p> <ol style="list-style-type: none"> 1. Apply MAXUM-PREP™ Spray Formula Deck & Wood Stripper liberally and evenly with a MAXUM® Pump Style Sprayer at a rate not to exceed 150 square feet per gallon. On vertical surfaces apply from the bottom to the top. DO NOT APPLY IN DIRECT SUNLIGHT OR TO HOT SURFACES. If drying does occur, mist surface lightly with water and reapply stripper. 2. Allow Spray Formula Deck & Wood Stripper to work for approximately 5-15 minutes or until the coating has softened or lifted. 3. Agitate surface with a stiff deck brush as required to loosen coating. 4. Rinse surface thoroughly with a garden hose or power washer. A power washer will eliminate the need for agitation. NOTE: To avoid damage to the wood surface if using a power washer, DO NOT EXCEED 1000 PSI and always work in the direction of the grain. Additional applications may be needed to completely remove all coatings. 5. To brighten and neutralize Cedar, Redwood and other tannin bleeding woods, we recommend neutralizing the surface with MAXUM-PREP Wood Brightener within 2-3 days of stripping. 6. To neutralize the pH of the wood surface after stripping, wash surface thoroughly with MAXUM-PREP™ Mill Glaze remover as per label instructions. <p>Allow surface to dry 1-2 hours before applying MAXUM® Acrylic Sheer Naturals or MAXUM® Acrylic Semi-Transparent Deck & Siding Stain. If using MAXUM® Oil Based Sheer Naturals or MAXUM® Oil Based Semi-Transparent Deck and Siding Stain, allow surface to dry for 24-48 hours before applying stain.</p>	
APPEARANCE:	Purple Liquid	
PACKAGING:	1-Gallon (3.78L)	
APPLICATION TEMPERATURE:	MIN: 50°F MAX: 90°F	
STORAGE TEMPERATURE:	MIN: 40°F MAX: 100°F	
THINNING:	No Thinning Necessary, If required, use Water	

WEIGHT PER GALLON:	8.85 lbs.
FLASH POINT:	Over 200°F
pH:	13.5
*NOTE ON SPREAD RATE:	Actual spread rate will vary based upon numerous factors including texture of the substrate, application method, waste, surface porosity and thinning.
CAUTIONS:	<p style="text-align: center;">DANGER! Corrosive Liquid. Causes eye and skin burns. May cause allergic skin reaction.</p> <p>CONTAINS: Glycol Ether and Anhydrous Sodium Metasilicate. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Vapors or mists may cause irritation to the eyes, skin, nose, throat and upper respiratory tract. The Glycol Ether may be absorbed through the skin causing possible kidney and liver injury, and may cause blood abnormalities based on animal data. Harmful or fatal if swallowed.</p> <p>NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.</p> <p style="text-align: center;">Use Only With Adequate Ventilation</p> <p>Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.</p> <p>FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean contaminated shoes. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p>WARNING: This product contains chemical(s) known to the state of California to cause cancer and birth defects or other reproductive harm.</p> <p style="text-align: center;">Obtain and read the MSDS prior to use of this product. KEEP FROM FREEZING</p> <p style="text-align: center;">KEEP OUT OF REACH OF CHILDREN</p>
VOC/VOS STATEMENT:	Exempt

05/09