



101 Paragon Drive · Montvale, New Jersey 07645 · PHONE 800-883-4193 · FAX 800-394-9022

MAXUM-PREP™ PROFESSIONAL MULTI-PURPOSE CLEANER

Type	Dilution Ratio:	Theoretical Spread Rate	Recommended Application	Thinner	Clean Up
Cleaner	9:1	Up to 350 Sq. Ft. per Mixed Gallon*	Brush, MAXUM® Pump Style Sprayer, or Power Washer	Water	Water

PRODUCT NAME: M95-2003P MAXUM PREP™ Professional Multi-Purpose Cleaner	MAXUM-PREP™ Professional Multi-Purpose Cleaner – Is a highly concentrated biodegradable cleaner designed to remove dirt and chalk from aluminum, concrete, fiberglass, masonry, vinyl, and wood, surfaces quickly and easily with minimal scrubbing required. This acid free formula can also be used on painted and stained surfaces, glass, and metal windows without harming the finish. Multi-Purpose cleaner is safe for pets, people, and vegetation when used properly and according to manufacturers' instructions.	
WHERE TO USE:	Concrete Vinyl Aluminum Painted Surfaces Fiberglass	MAXUM-PREP™ Professional Multi-Purpose Cleaner can be used to remove dirt and chalk from aluminum, concrete, fiberglass, masonry, vinyl, and wood, surfaces quickly and easily with minimal scrubbing required.
SURFACE PREPARATION:	Before applying MAXUM-PREP™ Professional Multi-Purpose cleaner wet down surface prior to application. DO NOT apply to a dry or hot surface.	
APPLICATION:	<p>Prior to application test product in an inconspicuous area and allow to dry thoroughly before use. Surface must be dry and above 50°F.</p> <p>Do not apply when air and surface temperatures are below 50°F or above 100°F.</p> <ol style="list-style-type: none"> Determine best dilution ratio by testing before general use. Start with 1 part cleaner to 9 parts water and adjust accordingly. All purpose cleaner is set up for direct use in a 9:1 Power Washer soap injector. After proper dilution is established, prepare enough solution for the area to be cleaned. Before applying solution to surface, wet surface with water. Apply mixed solution to surface by brush, roller, MAXUM® pump style sprayer, or power washer at a rate not to exceed 350 square feet per mixed gallon. Always apply cleaner from the bottom up to avoid streaking. DO NOT apply solution in direct sunlight or to hot surfaces. Let the solution stand for 3-5 minutes. DO NOT allow surface to dry. Thoroughly rinse surface with clean fresh water. Heavily soiled areas may require a second application and possible agitation. 	
APPEARANCE:	Green Liquid	
PACKAGING:	1-Gallon (3.78L)	
APPLICATION TEMPERATURE:	MIN: 50°F MAX: 90°F	
STORAGE TEMPERATURE:	MIN: 40°F MAX: 100°F	
THINNING:	Maximum 9-parts Water to 1-part Cleaner	
WEIGHT PER GALLON:	8.85 lbs.	
FLASH POINT:	Over 200°F	
pH:	13.5	
*NOTE ON SPREAD RATE:	Actual spread rate will vary based upon numerous factors including texture of the substrate, application method, waste, surface porosity and thinning.	

<p>CAUTIONS:</p>	<p style="text-align: center;">WARNING! VAPOR HARMFUL. CAUSES EYE AND SKIN IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL IF SWALLOWED.</p> <p>Contains: Monoethanolamine, Trisodium Nitrotriacetate, and Glycol Ethers, which have been found to cause adverse reproductive effects in laboratory animals. Nitrotriacetic acid and its salts have been classified as a human carcinogen. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. 2-Butoxyethanol may be absorbed through the skin causing possible kidney and liver injury. Individuals with chronic pulmonary, skin, kidney or liver diseases must not handle this material. Harmful if swallowed.</p> <p>NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep container tightly closed. Store in a cool, well ventilated area. Do not store in aluminum or copper containers.</p> <p>Use only with adequate ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not get in eyes, on skin or clothing. Wash thoroughly after handling.</p> <p>First Aid: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes.</p> <p>Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean contaminated shoes. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p>WARNING: This product contains a chemical known to the state of California to cause cancer.</p> <p style="text-align: center;">KEEP FROM FREEZING</p> <p style="text-align: center;">OBTAIN & READ MSDS PRIOR TO USING PRODUCT KEEP OUT OF REACH OF CHILDREN</p>
<p>VOC/VOS STATEMENT:</p>	<p>Exempt</p>

05/09