
INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

EP-5900

attention if persistent irritation and/or a skin rash, appears. Do not reuse clothing until thoroughly cleaned.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

INGESTION: DO NOT INDUCE VOMITING. In general, no treatment is necessary unless large quantities of product is ingested. However, get medical advice.

NOTE TO PHYSICIAN:
Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification : Class IIIB
Flashpoint : 309.0 °F
Explosion Level : Low - -N/A
High - -N/A

EXTINGUISHING MEDIA

Water spray, dry chemical, carbon dioxide (CO₂), alcohol foam

FIRE-FIGHTING PROCEDURES AND EQUIPMENT

Clear fire area of unprotected personnel. Do not enter confined space without helmet, face shield, bunker coat, gloves, rubber boots, and a positive pressure NIOSH-approved self-contained breathing apparatus. Water spray may be used to cool closed containers to prevent pressure build-up and possible explosion when exposed to extreme heat. Water may be ineffective in extinguishing a paint fire. Therefore, use caution not to spread flames with stream of water. If water is used, fog nozzles are preferable.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Heating this product above 300 Deg F in the presence of air may cause slow oxidative decomposition above 500 Deg F, polymerization may occur. Some curing agents, e.g., aliphatic polyamines can produce exothermic reactions which in large masses can cause runaway polymerization and charring of the reactants. Do not breathe fumes.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP:

Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions.

*** SMALL SPILLS ***

Take up with an absorbent material and place in non-leaking containers; seal tightly for proper disposal.

SPILL OR LEAK PROCEDURES:

May burn although not readily ignitable. Use cautious judgement when cleaning up large spills.

*** LARGE SPILLS ***

Wear respirator and protective clothing as appropriate. Shut off source of leak if safe to do so. Dike and contain. Remove with vacuum trucks or pump to storage vessels.

SECTION 7 - HANDLING AND STORAGE

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

EP-5900

HANDLING

Handle in accordance with the hazard potential of curing agent(s) used. **WARNING:** May cause skin and eye irritation. May cause skin sensitization. Avoid contact with eyes. Avoid prolonged or repeated contact with skin.

STORAGE

Store in a cool, dry place. Keep away from open flames and high temperatures. Containers, even those that have been emptied, can contain hazardous product residues.

SPECIAL COMMENTS

Avoid all bodily contact. Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Launder contaminated clothing before reuse. Contaminated leather shoes cannot be decontaminated and should be destroyed to prevent reuse.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to chemicals in Section 2 is maintained below applicable exposure limits.

RESPIRATORY PROTECTION:

Refer to Section 5.

EYE PROTECTION:

Avoid contact with eyes. Wear safety glasses or goggles as appropriate.

PROTECTIVE GLOVES:

Do not get on skin, on clothing. Wear chemical-resistant protective clothing such as gloves, outer clothing or apron, over shoes and a face shield suitable to potential exposure.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| | |
|----------------------------------|------------------------------|
| Physical State | : LIQUID |
| Vapor Pressure | : 13.30 |
| Vapor Density | : -N/A |
| Boiling Point Range | : Lower - 500.0 °F |
| | : Higher - 300.0 °F |
| Specific Gravity | : 1.110 |
| Weight per Volume | : 9.2432 LB/GL |
| VOC - Total (lbs./gal) | : .022 |
| Evaporation Rate | : .000 (n-Butyl Acetate = 1) |
| Volatile by Weight | : .2413 |
| Volatile by Volume | : .3392 |

SECTION 10 - STABILITY AND REACTIVITY

MATERIALS TO AVOID

Can react vigorously with strong oxidizing agents, strong Lewis or mineral acids, and strong mineral and organic bases, especially primary and secondary aliphatic amines.

HAZARDOUS POLYMERIZATION: May occur.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide, aldehydes, acids, and other organic substances may be formed during combustion or elevated (> 500 Deg F) temperature degradation.

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

EP-5900

CONDITIONS TO AVOID

Reaction with some curing agents may produce considerable heat.
STABILITY: Stable.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Discharge, treatment, or disposal may be subject to national, state or local laws. We recommend that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : N/A
DOT PACKAGING GROUP : N/A
DOT LABEL : NONE
DOT SHIPPING NAME : NOT REGULATED
DOT PLACARD : NONE
UN/NA NUMBER : NONE

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SECTION 16 - OTHER INFORMATION

Prepared by : INSL-X PRODUCTS CORP.
Date of issue : 02/08/2006
Last Revision Date : NONE
MSDS Prepared for :

MSDS Last Prepared : NONE
HMIS Rating: Health- 2 Flammability- 1
 Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g) (4).
The above information pertains to this product as currently formulated

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

EP-5900

and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.