





-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET  
-----

EP-59BG

-----  
**\*\*\* LARGE SPILLS \*\*\***

Eliminate potential sources of ignition. Wear appropriate respirator and other protective clothing. Shut off source of leak only if safe to do so. Dike and contain. Remove with vacuum trucks or pump to storage vessels. Soak up residue with an absorbent such as clay, sand, or other suitable material; place in non-leaking containers and seal tightly for proper disposal.

-----  
SECTION 7 - HANDLING AND STORAGE  
-----

HANDLING

Keep liquid and vapor away from heat, sparks and flame. Surfaces that are sufficiently hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone. Vapors may accumulate and travel to ignition sources distant from the handling site; flash-fire can result. Keep containers closed when not in use. Use with adequate ventilation.

STORAGE

Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize drum containers to empty them.

SPECIAL COMMENTS:

Containers, even those that have been emptied, can contain hazardous product residues. Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Launder contaminated clothing before reuse. Contaminated leather shoes cannot be decontaminated and should be destroyed to prevent reuse.

-----  
SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION  
-----

ADDITIONAL PROTECTIVE MEASURES

Use explosion-proof ventilation as required to control vapor concentrations. Eye wash fountains and safety showers should be available for emergency use.

RESPIRATORY PROTECTION

Avoid breathing dust/mists. If exposure may or does exceed occupational exposure limits, use a NIOSH-approved respirator to prevent overexposure. Avoid breathing vapors, which may be produced under some conditions such as heating or applications of uncured product in large surface areas (e.g., flooring and painting). Avoid breathing aerosols and mists which may be formed by various methods of application.

EYE PROTECTION:

Avoid contact with eyes. Wear safety glasses or goggles as appropriate.

PROTECTIVE GLOVES:

Avoid prolonged or repeated contact with skin. Wear chemical resistant gloves and other clothing, as required, to minimize contact.

-----  
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES  
-----

Appearance . . . . . : VERY LIGHT YELLOW COLOR  
Physical State . . . . . : LIQUID  
Vapor Pressure . . . . . : -N/A  
Vapor Density . . . . . : -N/A  
Boiling Point Range . . . . . : Lower - -N/A      øf

-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET  
-----

EP-59BG

-----  
Higher - 400.0 øF  
Specific Gravity . . . . . : 1.021  
Weight per Volume . . . . . : 8.5000 LB/GL  
VOC - Total (lbs./gal) . . . . . : .000  
Evaporation Rate . . . . . : .000 (n-Butyl Acetate = 1)  
Volatile by Weight . . . . . : .0000  
Volatile by Volume . . . . . : .0000  
-----

SECTION 10 - STABILITY AND REACTIVITY

-----  
INCOMPATIBILITIES (Materials to Avoid)

This product can react violently with strong oxidizing agents and strong acids.

HAZARDOUS POLYMERIZATION

Will not occur.

CONDITIONS TO AVOID

Avoid heat and flames. Can react vigorously with strong oxidizing agents, strong Lewis or mineral acids, and strong mineral and organic bases (especially primary and secondary aliphatic amines). Reaction with some curing agents may produce considerable heat.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide, aldehydes, acids, and other organic substances may be formed during combustion or elevated (> 500 Deg F) temperature degradation.

STABILITY: Stable.

-----  
SECTION 11 - TOXICOLOGICAL INFORMATION  
-----

No data at this time.

-----  
SECTION 12 - ECOLOGICAL INFORMATION  
-----

No data at this time.

-----  
SECTION 13 - DISPOSAL CONSIDERATIONS  
-----

DISPOSAL CONSIDERATION

Consult an expert on disposal of recovered product and ensure conformity to local disposal regulations.

-----  
SECTION 14 - TRANSPORT INFORMATION  
-----

DOT HAZARD CLASS . . . . . : NOT REGULATED (In containers less than 119 gallons or 450 liters via surface transportation).  
COMBUSTIBLE LIQUID (In containers of more than 119 gallons capacity) for surface shipments within the U.S. and Canada, and apply the DOT information, listed below:

DOT SHIPPING NAME . . . . . : PAINT  
DOT PACKAGING GROUP . . . . . : PG III  
DOT LABEL . . . . . : NONE  
DOT PLACARD . . . . . : NONE  
UN/NA NUMBER . . . . . : UN1263  
-----

SECTION 15 - REGULATORY INFORMATION  
-----

-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET  
-----

EP-59BG  
-----

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.  
-----

SECTION 16 - OTHER INFORMATION  
-----

Prepared by . . . . . : INSL-X PRODUCTS CORP.  
Date of issue . . . . . : 02/08/2006  
Last Revision Date . . . . . : NONE  
MSDS Prepared for . . . . . :

MSDS Last Prepared . . . . . : NONE  
HMIS Rating:           Health- 3           Flammability- 1  
                          Reactivity- 0

\*\*\*\*\*

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

\*\*\*\*\*

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m3 or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.