



TAB #12
 Super Dampwall
 Gloss Enamel
 SE-0410
 Rev. 03/09

Super Dampwall Gloss Enamel SE-0410

Type	Sheen	Theoretical Spread Rate	Recommended Application	Thinner	Clean Up
Alkyd	High Gloss	400 - 450 Sq. Ft. Per Gallon*	Brush, Roller or Spray	TH-0202	TH-0202
Dry Time:		Tack Free: 4 Hrs.	Recoat: 12 Hrs.	Full Cure: 3 Days	

PRODUCT NAME: SE-0410 Super Dampwall Gloss Enamel	Super Dampwall is a non-toxic, odorless coating formulated with special resins designed especially for use on walls and ceilings in dairies and food processing plants. Can be applied to damp surfaces. However, this product is not for immersion service.				
WHERE TO USE:	Interior	Interior Walls and Ceilings of: Dairies Bottling Plants Showers Food Lockers Hospitals Laundries Canneries Breweries Restaurants			
SURFACE PREPARATION:	<p>General – All surface areas to be painted should be clean, sound and free of all dirt, grease, oils, waxes, mildew and any other surface contaminants that can cause paint failure. Dirt and chalk should be thoroughly removed by scrubbing with warm soapy water. Surface wax should be removed with a commercial wax stripper. Grease residue should be removed with INSL-X® Citri-Clean. Remove all loose chipping, cracking and peeling from previously painted surfaces by hand scraping, or sanding. All glossy surface areas should be lightly sanded to effectively dull any existing sheen and create a more suitable surface for painting.</p> <p>Mildew – Surface areas affected by mildew should be thoroughly hand scrubbed with a soft to medium bristle scrub brush and a solution of one cup Tri-Sodium Phosphate or a non-ammoniated detergent cleaner mixed with one part household bleach and three parts warm water, per gallon solution, Allow solution to stand on the affected surface areas for approximately 10 – 20 minutes, then rinse thoroughly with clean water and allow 24 – 48 hours to dry.</p> <p>Super Dampwall is self-priming, showing good adhesion to masonry, wood and plasterboard. Do not use on galvanized metal.</p>				
*NOTE ON SPREAD RATE:	Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning. The Theoretical Spread Rate listed on this document has not taken into account these factors and is only based upon the volume solids of this product and the recommended wet film thickness when applied to a smooth substrate.				
APPLICATION:	<p>Super Dampwall applies easily with a quality brush or roller; and by spray application. Stir product thoroughly before using. It is important to maintain a wet edge during all methods of paint application by brushing or rolling into previously applied coating area. Apply when surface and ambient temperature are above 55° F and below 90° F. Do not paint if surface temperature is within 5° F of the dew point.</p> <p>This product is formulated to be applied without thinning. Do not thin if this would result in the product exceeding any VOC regulations in effect where it is being applied.</p> <p>Brush: Synthetic Bristle only. Roller: ½" Lambs Wool or Short Nap Synthetic Cover (Less than ½").</p>				

TAB #12
Super Dampwall
Gloss Enamel
SE-0410
Rev. 03/09

COLORS / TINTABILITY:	Super Dampwall is available in White only. Do not tint.	
RESIN TYPE:	Alkyd Resin	
SOLIDS:	Weight – 71.5 ± 1.0% Volume – 54.0 ± 1.0%	
WEIGHT PER GALLON:	10.3 lbs.	
VISCOSITY:	80 – 90 KU (Krebs Units)	
FLASH POINT:	104° F or greater (TT-P-141, Method 4293)	
SPECULAR GLOSS:	80+ units @ 60 degrees	
PERFORMANCE:	Cross Hatch Adhesion (ASTM D3359): 5 Conical Mandrel Flexibility (ASTM D522): Passes ¼"	
REC. FILM THICKNESS:	Wet:	3.6 to 4.0 mils
	Dry:	1.9 to 2.2 mils
CAUTIONS:	<p style="text-align: center;">CAUTION! Contains Xylene, Aromatic Solvents, and Ethylbenzene. COMBUSTIBLE LIQUID AND VAPOR. HARMFUL IF INHALED. HARMFUL OR FATAL IF SWALLOWED. May be harmful if absorbed through skin. Causes eye, nose, throat and skin irritation. OVEREXPOSURE MAY CAUSE KIDNEY DAMAGE.</p> <p>NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvent with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.</p> <p>Use only with adequate ventilation. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Do not get in eyes, on skin or clothing. Wash thoroughly after handling. Keep away from heat, sparks and flame. Vapors can cause flash fire. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.</p> <p>First Aid: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.</p> <p>If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.</p> <p>DANGER – Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed, water-filled metal container.</p> <p>WARNING: This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.</p> <p style="text-align: center;">Obtain and read the MSDS prior to using this product. KEEP OUT OF REACH OF CHILDREN</p>	
VOC/VOS STATEMENT:	This product contains a maximum of 360 grams VOC/VOS per liter of coating. (2.83 pounds per gallon).	
OTC CATEGORY:	This product is not compliant under the Ozone Transport Commission regulations.	